

§ 408.300

**Subpart AD—Non-Alaskan Scallop Processing Subcategory**

SOURCE: 40 FR 55797, Dec. 1, 1975, unless otherwise noted.

**§ 408.300 Applicability; description of the non-Alaskan scallop processing subcategory.**

With the exception of land-based processing of calico scallops, the provisions of this subpart are applicable to discharges resulting from the processing of scallops outside of Alaska.

**§ 408.301 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

(b) The term *product* shall mean the weight of the scallop meat after processing.

**§ 408.302 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kkg of product)		
TSS .....	6.0	1.4
Oil and grease .....	7.7	0.24
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
English units (lb/1,000 lb of product)		
TSS .....	6.0	1.4
Oil and grease .....	7.7	0.24
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

**40 CFR Ch. I (7–1–00 Edition)**

[40 FR 55797, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

**§ 408.303 [Reserved]**

**§ 408.304 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
BOD5 .....	No limitation.
TSS .....	Do.
pH .....	Do.
Oil and grease .....	Do.

[40 FR 55797, Dec. 1, 1975, as amended at 60 FR 33948, June 29, 1995]

**§ 408.305 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/kkg of product)		
TSS .....	5.7	1.4
Oil and grease .....	7.3	0.23
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
English units (lb/1,000 lb of product)		
TSS .....	5.7	1.4
Oil and grease .....	7.3	0.23
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

**§ 408.306 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned